Received Fax :

29/08/03

14:37

PATENTANWÄLTE SIEGEN → 718 601 1099

NR. 579

D12

28/08/03

11:26

PATENTANUALTE SIEGEN + +49 2161 350866

NR. 565 **D**13

22644

12

13

16

I CLAIM!

- ì 1. A drive for reciprocating a roll stand of a pilger cold-rolling system, the drive comprising: 2 3 a crank rotatable about an axis transverse to a
- reciprocation direction of the stand;
- a tie rod having an outer end journaled on the stand and an inner and eccentrically journaled on the crank, whereby rotation of the crank reciprocates the stand in the direction; 7
- a compensating weight fixed to the crank opposite the tie rod and orbiting in a weight plane on rotation of the orank, •
- a counterweight offset along the weight plane from the 10 crank; and 11
 - drive means connecting the counterweight to the crank for orbiting the counterweight in the weight plane on rotation of the crapic.
- 2. The pilger roll-stand drive defined in claim 1. 1 further comprising 2
- respective shafts carrying the compensating weight and 3 counterwaight, the drive means including respective meshing gears 4 fixed to the shafts, 3

Received Fax : . . . AUG 29 2003 8:22 Fax Station : THE FIRM OF KARL F ROSS D . . 1

29/08/03 **28/08/03** 14:37 11:**27** PATENTANWALTE SIEGEN → 718 601 1099 PATENTANWALTE SIEGEN → +49 2161 350866

NR. 579 **D13** NR. **565 D14**

22644

- 3. The pilger roll-stand drive defined in claim 2 wherein the drive means further comprises
- a drive shaft carrying a gear meshing with the gear of the shaft carrying the counterweight.
- 4. The pilger roll-stand drive defined in claim 3

 wherein the shafts are rotatable about exes that are all coplanar

 and parallel.
- 5. The pilger roll-stand drive defined in claim 4 wherein the stand 10 centered on the weight plane.
- 6. The pilger roll-stand drive defined in claim 4 wherein the grank is centered on the weight plane.
- 7. The pilger roll-stand drive defined in claim 4,
 a further comprising
- a second crank coaxial with and connected to the firstmantioned crank;
- s second tie rod having an outer end journaled on the stand and an inner end eccentrically journaled on the second crank;

Received Fax : _ AUG 29 2003 8:22 Fax Station : THE FIRM OF KARL F ROSS

29/08/03 28/08/03 14:37 11:27 PATENTANWÄLTE SIEGEN → 718 601 1099 PATENTANWÄLTE SIEGEN → +49 2161 ,350866 NR. 579 D14

22644

.

•

10

11

12

13

14

15

16

a second compensating weight fixed to the second crank opposite the tie rod and orbiting in a second weight plane parallel to but offset from the first-mentioned weight plane on rotation of the cranks; and

a second counterweight offset along the second weight plane from the second crank, the drive means also connecting the second counterweight to the second crank for orbiting the second counterweight in the second weight plane on rotation of the second crank.

- 8. The pilger roll-stand drive defined in claim 7
 wherein the roll stand is centered on a plane symmetrically
 flanked by the first and second weight planes.
- 9. The pilger roll-stand drive defined in claim 7
 wherein the drive means is offset from the planes.
- 10. The pilger roll-stand drive defined in claim 4
 wherein the gears are unitarily formed with the respective
 weights.

Received Fax: AUG 29 2003 8:22 Fax Station: THE FIRM OF KARL F ROSS

29/08/03 **28/08/03** 14:38 11:**2**7 PATENTANWÄLTE SIEGEN → 718 601 1099
PATENTANWÄLTE SIEGEN → +49 2161 350866

NR. 579 P15

22544

1

2

3

1 ll. The pilger roll-stand drive defined in claim 4 wherein the shafts are horizontal.

1 12. The pilger roll-stand drive defined in claim 4 wherein the shafts are vertical.

13. The pilger roll-stand drive defined in claim 4 wherein the crank has a pin on which the inner end of the tie rod is journaled and that is formed with passages through which a lubricant can be fed.